


drawing no.	item no.	coating	feff	Hh	surface accuracy PV	roughness Ra
1-5-065-00-000 Pos.01	16836	uncoated	152,4	66,572	< 1µm	< 10nm
1-5-065-00-000 Pos.02	16837	Molybdenum	152,4	66,572	< 1µm	< 10nm
1-5-065-00-000 Pos.03	24167	Molybdenum	254	66,103	< 1µm	< 10nm
1-5-065-00-000 Pos.04	22745	Molybdenum	342,9	65,921	< 0,5µm	< 10nm
1-5-065-00-000 Pos.05	20146	Molybdenum	220,98	66,208	< 1µm	< 10nm
1-5-065-00-000 Pos.06	20147	Molybdenum	284,48	66,028	< 1µm	< 10nm
1-5-065-00-000 Pos.07	37473	Molybdenum	200	66,239	< 1µm	< 10nm

TOLERANCES UNL. STATED ISO 2768 mH			
1	Tabelle und Formgenauigkeit Pos.4 angepasst (13.8.14/gt)	13.07.16	AM
ISS.	MODIFY	DATE	NAME
	MATERIAL: OFHC-Cu	DRAWN	13.07.16
	SURFACE:	CHECKED	13.07.16
SCALE: 1:1	DESCRIPTION: PARABOLIC MIRROR	ITEM:	A3
SEMI-FINISHED PRODUCT:	ORIG.	REPL.F.	DRAWING NUMBER: 1-5-065-00-000-k.1
			SHEET: 1
			OF: 1

TOLERANCES UNL. STATED ISO 2768 mH



PROTECTION REFERENCE TO DIN 34 OBSERVE